

		Duramin-150
<b>Hardness methods</b>	Vickers	N.A.
	Knopp	N.A.
	Brinell	N.A.
	Rockwell - optional	ISO 6508 ASTM E18 JIS Z 2245
<b>Force range</b>	29.4-1471 N (3-150 kgf)	
<b>Test force</b>	Force application	Fully automatic, closed loop, force feedback, loading, dwell, unloading
	Test force tolerance	< 0.5 %
	Dwell time settings	Adjustable 1 to 99 s
<b>Turret</b>	1 Position	1
<b>Electrical data</b>	Power supply	100 V AC-240 V AC, 50/60Hz, single phase
	Power consumption max. work load	100 W
	Power consumption idle Power consumption Idle Power consumption idle	13 W
	Power consumption max. load Power consumption Max. load Power consumption max. load	100 W
	Power inlet	1-phase (N+L1+PE) or 2-phase (L1+L2+PE) The electrical installation must comply with Installation Category II
<b>Residual Current Circuit Breaker (RCCB)</b>	Type A, 30 mA is required depending on local regulations.	
<b>Dimensions</b>	Width	230 mm (9.1")
	Depth	550 mm (21.7")
	Height	855 mm (33.7")
<b>Weight</b>	115 kg (252 lbs)	
<b>Read method</b>	Automated	
<b>Overview camera resolution</b>	N.A.	
<b>Overview camera field of view</b>	N.A.	
<b>Measurement camera resolution</b>	N.A.	
<b>Positions in nosepiece</b>	1	
<b>Position in nosepiece for overview camera</b>		



		Duramin-150
<b>Max no. of Indenters</b>	Max no. of indenters	1
<b>Max No. of Objectives</b>	Max no. of objectives	N.A.
<b>Indenter Shaft</b>	Diameter	6.35
<b>Standard objectives included</b>		N.A.
<b>Z-Axis</b>		Manual
<b>Anti-collision protection</b>		
<b>XY Stage / Anvil</b>		Anvil
<b>Stage Size</b>		Ø60 mm (2.4")
<b>Stage Stroke (travel range)</b>		N.A.
<b>Auto Illumination</b>		No
<b>Stage Illumination</b>		Yes
<b>Laser/LED Guide</b>		No
<b>Software</b>	Operating software	Embedded
	Integrated PC	No
	Monitor	6.5" portrait mode capacitive touch screen
	Dual view	No
	Possibility to connect Printer	No
	Ethernet Connection	No
	Data Export	USB
<b>System</b>	Data output	TXT
<b>Software modules</b>		Total test, max, min, average, range, standard deviation, all in real time after each test
<b>Sample height</b>		240 mm (9.4")
<b>Throat depth</b>		150 mm (5.9")
<b>Safety standards</b>		CE labelled according to EU directives
<b>REACH</b>		For information about REACH. contact your local Struers office
<b>Operating environment</b>	Surrounding temperature	10-35°C (50-95°F)
	Humidity	10%-90% RH non-condensing



**TECHNICAL DATA**

**Duramin-150**

<b>Duramin-150</b>		
<b>Safety Circuit Categories/Performance Level</b>	Emergency stop	EN ISO 13849-1 PL c, Category 1 Stop category 0
<b>Noise level</b>	A-weighted sound emission pressure level at workstations	< 70 dB(A)
<b>Vibration level</b>	During operation	Total vibration exposure to upper parts of the body does not exceed 2.5 m/s <sup>2</sup> .

Doc. no.: 16687750\_A\_en  
Date of release: 30-06-2023