



		Laboforce-UI
<b>Safety standards/directives/legislation</b>		See the Declaration of Conformity/Instruction manual See the Declaration of Conformity/Instruction manual.
<b>REACH</b>		For information about REACH, contact your local Struers office.
<b>Operating environment</b>	Surrounding temperature	
	During operation	5-40 °C (41-104 °F)
	During transport	0-60 °C (32-104 °F)
	Humidity	< 85% RH non-condensing
<b>Power supply</b>	Voltage/frequency	1x24 V
	Power inlet	Connected directly to Labopol
	Current	
	Nominal	0.1 A
	Max.	0.1 A
	Current, largest load	0.1 A
<b>Dimensions and weight</b>	Width	15 cm (5.9")
	Depth	13.5 cm (5.3")
	Height	37.6 cm (14.8")
	Height (with open cover)	
	Weight	0.8 kg (1.8 lbs)
<b>Noise level</b>	A-weighted sound emission pressure level at workstations	see the Labopol technical data
<b>Noise level</b>	<p>The figures quoted are emission levels and are not necessarily safe working levels. While there is a correlation between the emission and exposure levels, this cannot be used reliably to determine whether or not further precautions are required. Factors that influence the</p> <p>actual level of exposure of the workforce include characteristics of the work room, the other sources of noise, etc., i.e. the number of machines and other adjacent processes. Also, the permissible exposure level can vary from country to country. This information, however, will</p> <p>enable the user of the machine to make a better evaluation of the hazard and risk.</p>	
<b>Vibration level</b>	Declared vibration emission	N/A