

SAFETY DATA SHEET



Product name: CALDOFIX-2 RESIN
Revision Date: 2019-12-03
Document No.: M0170

Page: 1/11
Print date: 2019-12-03
SDS-ID: AU-EN/14.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name: CALDOFIX-2 RESIN
Cat. No. 40200085, 40200084
Container size: 1 l

Relevant identified uses of the substance or mixture and uses advised against

Application: For embedding and impregnation of materialographic specimens
Uses advised against: No specific uses advised against are identified. (*)

Details of the supplier of the safety data sheet

Supplier: Struers Australia
27 Mayneview Street
Milton QLD 4064, Australia
Responsible for safety data sheet authoring: Responsible for safety data sheet authoring: DHI
Any questions to the contents of this safety data sheet should be sent to:
struers@struers.dk

Emergency telephone number

Australian Poisons Information Centre: 13 11 26.

+61 7 3512 9600
(Only during office hours)

SAFETY DATA SHEET

Product name: CALDOFIX-2 RESIN
Revision Date: 2019-12-03
Document No.: M0170

Page: 2/11
Print date: 2019-12-03
SDS-ID: AU-EN/14.0

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

WHS:
Skin corrosion/irritation - Category 2
Serious eye damage/eye irritation - Category 1
Skin Sensitisation - Category 1
Mutagenicity - Category 2
Chronic hazard to the aquatic environment - Category 2

Label elements



Danger

Contains:
Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)
Neodecanoic acid oxiranylmethylester
2-Propenoic acid, reaction products with pentaerythritol
Hexamethylene diacrylate

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H341 Suspected of causing genetic defects.
H411 Toxic to aquatic life with long lasting effects.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor/physician.

Other hazards

PBT/vPvB: No information available.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

The product contains: epoxy resin .

SAFETY DATA SHEET

Product name:	CALDOFIX-2 RESIN	Page:	3/11
Revision Date:	2019-12-03	Print date:	2019-12-03
Document No.:	M0170	SDS-ID:	AU-EN/14.0

WHS:

<u>%:</u>	<u>CAS-No.:</u>	<u>EC No.:</u>	<u>REACH Reg. No:</u>	<u>Chemical name:</u>	<u>Hazard classification:</u>	<u>Notes:</u>
60-100	25068-38-6	500-033-5	01-2119456619-26-xxxx	Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight <= 700)	Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Chronic 2;H411	
15-35	26761-45-5	247-979-2	01-2119431597-33-xxxx	Neodecanoic acid oxiranylmethylester	Skin Sens. 1;H317 Muta. 2;H341 Aquatic Chronic 2;H411	
1-5	13048-33-4	235-921-9	01-2119484737-22-xxxx	Hexamethylene diacrylate	Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317	D
1.5-2.5	3524-68-3	222-540-8	-	Pentaerythritol triacrylate	Acute Tox. 4;H302 Skin Irrit. 2;H315 Eye Dam. 1;H318 Skin Sens. 1;H317 Aquatic Chronic 2;H411	
1.5-2.5	4986-89-4	225-644-1	-	Pentaerythritol tetraacrylate	Acute Tox. 4;H302 Skin Irrit. 2;H315 Eye Dam. 1;H318 Skin Sens. 1;H317 Aquatic Chronic 2;H411	

References: The full text for all hazard statements is displayed in section 16.

SECTION 4: FIRST AID MEASURES

Description of first aid measures

Inhalation: Move injured person into fresh air and keep person calm under observation. If uncomfortable: Seek hospital and bring these instructions.

Skin contact: Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and bring these instructions.

Eye contact: Immediately flush with plenty of water. Remove any contact lenses and open eyes wide apart. Call an ambulance and continue flushing during transportation to hospital. Bring these instructions.

Ingestion: Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable seek hospital and bring these instructions. Do not induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms/effects: See section 11 for more detailed information on health effects and symptoms.

Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Treat symptomatically.

SAFETY DATA SHEET

Product name:	CALDOFIX-2 RESIN	Page:	4/11
Revision Date:	2019-12-03	Print date:	2019-12-03
Document No.:	M0170	SDS-ID:	AU-EN/14.0

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Extinguishing media: Extinguish with foam, carbon dioxide, dry powder or water fog. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Special hazards arising from the substance or mixture

Specific hazards: During fire, gases hazardous to health may be formed.

Advice for firefighters

Protective equipment for fire-fighters: Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Avoid contact with skin and eyes. For personal protection, see section 8.

For emergency responders: No specific recommendations. For personal protection, see section 8.

Environmental precautions

Environmental precautions: Avoid discharge into drains, water courses or onto the ground.

Methods and material for containment and cleaning up

Spill Cleanup Methods: Absorb spillage with suitable absorbent material.

Reference to other sections

References: For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Safe handling advice: Avoid contact with skin and eyes. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Observe good chemical hygiene practices.

Technical measures: Work practice should minimise contact. Technical aids: Use disposable equipment (rags, brushes, spatulas, putty knives, etc.), if possible.

Technical precautions: Local exhaust is recommended. First-aid equipment, including eye wash bottle, must be available at the work site.

Conditions for safe storage, including any incompatibilities

Technical measures for safe storage: No special precautions.

Storage conditions: Store in closed original container in a dry place.

Specific end use(s)

Specific use(s): No information available.

SAFETY DATA SHEET

Product name:	CALDOFIX-2 RESIN	Page:	5/11
Revision Date:	2019-12-03	Print date:	2019-12-03
Document No.:	M0170	SDS-ID:	AU-EN/14.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

No occupational exposure limit assigned.

Exposure controls

<u>Engineering measures:</u>	Local exhaust is recommended. Mix and prepare in a place with efficient exhaust ventilation. An eye wash bottle must be available at the work site. Provide access to washing facilities including soap, skin cleanser and fatty cream.
<u>Personal protection:</u>	Personal protection equipment should be chosen according to relevant AS/NZS standards and in discussion with the supplier of the personal protective equipment.
<u>Respiratory equipment:</u>	In case of inadequate ventilation and work of brief duration, use suitable respiratory equipment. It is recommended to use respiratory equipment with combination filter, type ABEK
<u>Hand protection:</u>	Wear protective gloves. Butyl rubber gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.
<u>Eye protection:</u>	Wear goggles/face shield.
<u>Skin protection:</u>	Wear apron or protective clothing in case of splashes.
<u>Hygiene measures:</u>	Remove contaminated clothing and wash the skin thoroughly with soap and water after work. When using do not eat, drink or smoke.
<u>Environmental Exposure Controls:</u>	Not available.

SAFETY DATA SHEET

Product name: CALDOFIX-2 RESIN
Revision Date: 2019-12-03
Document No.: M0170

Page: 6/11
Print date: 2019-12-03
SDS-ID: AU-EN/14.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance: clear yellowish liquid

Odour: slight odour

Odour threshold: Not available.

pH: Not available.

Melting point: Not available.

Boiling point: Not available.

Flash point: 110 °C

Evaporation rate: Not available.

Flammability (solid, gas): Not available.

Explosion limits: Not available.

Vapour pressure: Not available.

Vapour density: Not available.

Relative density: 1,13

Solubility: insoluble in water

Partition coefficient (n-octanol/water): Not available.

Auto-ignition temperature (°C): Not available.

Decomposition temperature (°C): Not available.

Viscosity: Not available.

Explosive properties: Not available.

Oxidising properties: Not available.

Other information

Other data: Volatile Organic Compound (VOC): 0 g/l

SAFETY DATA SHEET

Product name: CALDOFIX-2 RESIN
Revision Date: 2019-12-03
Document No.: M0170

Page: 7/11
Print date: 2019-12-03
SDS-ID: AU-EN/14.0

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Reactivity: No data available.

Chemical stability

Stability: Stable under normal temperature conditions.

Possibility of hazardous reactions

Hazardous Reactions: No data available.

Conditions to avoid

Conditions/materials to avoid: Strong oxidising substances and strong bases.

Incompatible materials

Incompatible materials: No information available.

Hazardous decomposition products

Hazardous decomposition products: None under normal conditions.

SAFETY DATA SHEET

Product name:	CALDOFIX-2 RESIN	Page:	8/11
Revision Date:	2019-12-03	Print date:	2019-12-03
Document No.:	M0170	SDS-ID:	AU-EN/14.0

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects

<u>Acute Toxicity (Oral):</u>	Based on available data, the classification criteria are not met.
<u>Acute Toxicity (Dermal):</u>	Based on available data, the classification criteria are not met.
<u>Acute Toxicity (Inhalation):</u>	Based on available data, the classification criteria are not met.
<u>Skin Corrosion/Irritation:</u>	Causes skin irritation.
<u>Serious eye damage/irritation:</u>	Causes serious eye damage.
<u>Respiratory or skin sensitisation:</u>	May cause an allergic skin reaction.
<u>Germ cell mutagenicity:</u>	Suspected of causing genetic defects.
<u>Carcinogenicity:</u>	Based on available data, the classification criteria are not met. National Toxicology Program (NTP): No. I.A.R.C. Monographs: No.
<u>Reproductive Toxicity:</u>	Based on available data, the classification criteria are not met.
<u>STOT - Single exposure:</u>	Based on available data, the classification criteria are not met.
<u>STOT - Repeated exposure:</u>	Based on available data, the classification criteria are not met.
<u>Aspiration hazard:</u>	Based on available data, the classification criteria are not met.
<u>Inhalation:</u>	Not relevant at normal room temperatures. When heated, irritating vapours may be formed.
<u>Ingestion:</u>	Irritating. May cause nausea, stomach pain and vomiting.
<u>Toxicological data:</u>	Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700): Acute Toxicity (Oral LD50): 11400 mg/kg (Rat) Acute Toxicity (Dermal LD50): 2000 mg/kg (Rat) Neodecanoic acid oxiranylmethylester: Acute Toxicity (Oral LD50): 9600 mg/kg (Rat) Acute Toxicity (Dermal LD50): 3800 mg/kg (Rat)

SAFETY DATA SHEET

Product name:	CALDOFIX-2 RESIN	Page:	9/11
Revision Date:	2019-12-03	Print date:	2019-12-03
Document No.:	M0170	SDS-ID:	AU-EN/14.0

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecotoxicity: Toxic to aquatic life with long lasting effects.

Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700): 1.3 (LC50 96 hours, fish, mg/l) (*)

Neodecanoic acid oxiranylmethylester: 9.6 (LC50 96 hours, fish, mg/l) (*)

Persistence and degradability

Degradability: This product is expected to be not readily biodegradable.

Bioaccumulative potential

Bioaccumulative potential: May accumulate in soil and water systems.

Mobility in soil

Mobility: No data available.

Results of PBT and vPvB assessment

PBT/vPvB: No information available.

Other adverse effects

Other adverse effects: No information available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues: Dispose of waste and residues in accordance with local authority requirements.
For personal protection, see section 8.
Hazardous characteristics of waste: H12 (Ecotoxic)
Note that fully cured material is not considered as hazardous waste.

Contaminated packaging: Dispose of waste and residues in accordance with local authority requirements.

SAFETY DATA SHEET

Product name:	CALDOFIX-2 RESIN	Page:	10/11
Revision Date:	2019-12-03	Print date:	2019-12-03
Document No.:	M0170	SDS-ID:	AU-EN/14.0

SECTION 14: TRANSPORT INFORMATION

UN number

UN-No: 3082

UN proper shipping name

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)

Additional IMDG information:
EmS: F-A , S-F
MFAG:1

Transport hazard class(es)

Class: 9

Packing group

PG: III

Environmental hazards

Marine pollutant: Yes.

Environmentally Hazardous substance: Yes.

Special precautions for user

Special precautions: None known.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk: Not relevant.

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Special provisions: AICS: Listed.

National regulation: Work Health and Safety Regulations 2011, with amendments.
National model Code of Practice for the Labelling of Workplace Hazardous Chemicals (2018).
National model Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals (2011), with amendments.
Hazardous Waste (Regulation of Exports and Imports) Act 1989, with amendments.
The Industrial Chemicals (Notification and Assessment) Act 1989, as amended.

SAFETY DATA SHEET

Product name:	CALDOFIX-2 RESIN	Page:	11/11
Revision Date:	2019-12-03	Print date:	2019-12-03
Document No.:	M0170	SDS-ID:	AU-EN/14.0

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

The following sections contain revisions or new statements: 1.

The (*) indicates the changes made with respect to the previous version.

Approved by DHI.



Abbreviations and acronyms used in the safety data sheet: PBT = Persistent, Bioaccumulative and Toxic.
vPvB = very Persistent and very Bioaccumulative.

Additional information: Classification according to WHS Regulations 2011:
Calculation method.

Wording of H-statements:

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H341	Suspected of causing genetic defects.
H411	Toxic to aquatic life with long lasting effects.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark.
www.dhigroup.com.
