

# SAFETY DATA SHEET



|                |                     |             |            |
|----------------|---------------------|-------------|------------|
| Product name:  | DP-LUBRICANT YELLOW | Page:       | 1/12       |
| Revision Date: | 2018-11-07          | Print date: | 2018-11-07 |
| Document No.:  | M0119               | SDS-ID:     | CA-EN/19.0 |

---

## 1. IDENTIFICATION

### Product identifier

Product name: DP-LUBRICANT YELLOW  
Cat. No. 40700030

Container size: 1 l

### Recommended use and restrictions on use

Application: Cooling and lubricating agent for grinding and polishing of metallographic specimens.

### Details of the supplier of the safety data sheet

Supplier: Struers Ltd  
7275 West Credit Avenue  
Ontario L5N 5M9 Mississauga  
Canada  
Tel: +1 (905) 8148855

Responsible for safety data sheet authoring: Responsible for safety data sheet authoring: DHI  
Any questions to the contents of this safety data sheet should be sent to:  
struers@struers.dk

### Emergency telephone number

Alberta & NWT:  
Poison & Drug Information Service (PADIS): 1-800-332-1414  
British Columbia:  
Drug and Poison Information Centre (DPIC): 604-682-5050 / 1-800-567-8911  
Ontario:  
Poison Centre: 1-800-268-9017  
Québec:  
Poison Control Centre: 1-800-463-5060  
  
Infotrac:  
1-800-535-5053  
Struers CAN:  
+1 (905) 8148855  
(Only during office hours)

# SAFETY DATA SHEET

|                |                     |             |            |
|----------------|---------------------|-------------|------------|
| Product name:  | DP-LUBRICANT YELLOW | Page:       | 2/12       |
| Revision Date: | 2018-11-07          | Print date: | 2018-11-07 |
| Document No.:  | M0119               | SDS-ID:     | CA-EN/19.0 |

## 2. HAZARDS IDENTIFICATION

### Classification of the hazardous product

WHMIS 2015: Flammable Liquids — Category 2  
Eye Irritation — Category 2

### Label elements



#### Danger

|                    |  |
|--------------------|--|
| H225               | Highly flammable liquid and vapour.  |
| H319               | Causes serious eye irritation.   |
| P210               | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.                                   |
| P280               | Wear protective gloves, eye and face protection.   |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P337 + P313        | If eye irritation persists: Get medical advice/attention.  |
| P501               | Dispose of contents/container in accordance with local regulations.  |
|                    |  |
| P233               | Keep container tightly closed.   |
| P240               | Ground and bond container and receiving equipment.   |
| P241               | Use explosion-proof electrical, ventilating and lighting equipment.  |
| P242               | Use non-sparking tools.  |
| P243               | Take action to prevent static discharges.  |
| P264               | Wash contaminated skin thoroughly after handling.  |
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.                                     |
| P370 + P378        | In case of fire: Use alcohol resistant foam, carbon dioxide or dry powder to extinguish.   |
| P403 + P235        | Store in a well-ventilated place. Keep cool.   |

### Other hazards

PBT/vPvB: No information available.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Mixtures

The product contains: organic solvents, lubricants and pigments.

# SAFETY DATA SHEET

|                |                     |             |            |
|----------------|---------------------|-------------|------------|
| Product name:  | DP-LUBRICANT YELLOW | Page:       | 3/12       |
| Revision Date: | 2018-11-07          | Print date: | 2018-11-07 |
| Document No.:  | M0119               | SDS-ID:     | CA-EN/19.0 |

## WHMIS 2015:

| %:    | CAS-No.: | EC No.:   | REACH Reg. No:        | Chemical name: | Hazard classification:  | Notes: |
|-------|----------|-----------|-----------------------|----------------|---|--------|
| 50-90 | 64-17-5  | 200-578-6 | 01-2119457610-43-xxxx | Ethanol        | Flammable Liquids<br>Category 2<br>Eye Irritation Category 2  |        |
| 5-<10 | 67-63-0  | 200-661-7 | 01-2119457558-25-xxxx | Propan-2-ol    | Flammable Liquids<br>Category 2<br>Eye Irritation Category 2<br>Specific Target Organ<br>Toxicity Single Exposure<br>Category 3 |        |
| <0.1  | -        | -         | -                     | Pigment        | -   |        |

## 4. FIRST-AID MEASURES

### Description of first-aid measures

**Burns:** Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

**Inhalation:** Move injured person into fresh air and keep person calm under observation. If uncomfortable: Seek hospital and take along these instructions.

**Skin contact:** Remove contaminated clothes and rinse skin thoroughly with water.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Continue flushing during transport to hospital. Bring along these instructions.

**Ingestion:** Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable seek hospital and bring these instructions.

### Most important symptoms and effects, both acute and delayed

**Symptoms/effects:** See section 11 for more detailed information on health effects and symptoms.

### Indication of any immediate medical attention and special treatment needed

**Medical attention/treatments:** Treat symptomatically.

# SAFETY DATA SHEET

|                |                     |             |            |
|----------------|---------------------|-------------|------------|
| Product name:  | DP-LUBRICANT YELLOW | Page:       | 4/12       |
| Revision Date: | 2018-11-07          | Print date: | 2018-11-07 |
| Document No.:  | M0119               | SDS-ID:     | CA-EN/19.0 |

---

## 5. FIRE-FIGHTING MEASURES

### Extinguishing media

Extinguishing media: Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

### Specific hazards arising from the hazardous product

Specific hazards: The product is highly flammable, and explosive vapors/air mixtures may be formed even at normal room temperatures. Vapors may be ignited by a spark, a hot surface or an ember.

### Advice for fire-fighters

Protective equipment for fire-fighters: Use air-supplied respirator during fire fighting.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Protective equipment: Do not smoke or use open fire, or other sources of ignition. Avoid inhalation of vapors and contact with skin and eyes. For personal protection, see section 8. (\*)

Emergency procedures: No specific recommendations. For personal protection, see section 8. (\*)

### Environmental precautions

Environmental precautions: Do not discharge into drains, water courses or onto the ground.

### Methods and material for containment and cleaning up

Spill Cleanup Methods: Large quantities of concentrate should not be discharged into the drain but removed with absorbing material. Do not use sawdust or other combustible material.

### Reference to other items

References: For personal protection, see section 8. For waste disposal, see section 13.

---

# SAFETY DATA SHEET

|                |                     |             |            |
|----------------|---------------------|-------------|------------|
| Product name:  | DP-LUBRICANT YELLOW | Page:       | 5/12       |
| Revision Date: | 2018-11-07          | Print date: | 2018-11-07 |
| Document No.:  | M0119               | SDS-ID:     | CA-EN/19.0 |

---

## 7. HANDLING AND STORAGE

### Precautions for safe handling

Safe handling advice: Avoid inhalation of vapors and contact with skin and eyes. Observe good chemical hygiene practices. Take precautionary measures against static discharges.

Technical measures: Do not smoke or use open fire or other sources of ignition.

Technical precautions: Local exhaust is recommended.

### Conditions for safe storage, including any incompatibilities

Technical measures for safe storage: Follow rules for flammable liquids.

Storage conditions: Store in a cool and well-ventilated place. Avoid contact with oxidizing agents.

### Specific end-use(s)

Specific use(s): No information available.

---

# SAFETY DATA SHEET

|                |                     |             |            |
|----------------|---------------------|-------------|------------|
| Product name:  | DP-LUBRICANT YELLOW | Page:       | 6/12       |
| Revision Date: | 2018-11-07          | Print date: | 2018-11-07 |
| Document No.:  | M0119               | SDS-ID:     | CA-EN/19.0 |

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

Other provincial OEL's may apply.

Occupational exposure limits:

| <u>CAS-No.:</u> | <u>Chemical name:</u> | <u>As:</u> | <u>Exposure limits:</u> |            | <u>Type:</u> | <u>Notes:</u> | <u>References:</u> |
|-----------------|-----------------------|------------|-------------------------|------------|--------------|---------------|--------------------|
| 64-17-5         | Ethyl alcohol         | -          | 1000 ppm                | 1880 mg/m3 | TWA          | -             | Alberta            |
| 64-17-5         | Ethanol               | -          | 1000 ppm                |            | STEL         | -             | BC                 |
| 64-17-5         | Ethyl alcohol         | -          | 1000 ppm                | 1880 mg/m3 | TWA          | -             | Quebec             |
| 67-63-0         | Isopropyl alcohol     | -          | 400 ppm                 | 985 mg/m3  | TWA          | -             | Quebec             |
|                 |                       | -          | 500 ppm                 | 1230 mg/m3 | STEL         | 15min         |                    |
| 67-63-0         | Isopropyl alcohol     | -          | 200 ppm                 | 492 mg/m3  | TWA          | -             | Alberta            |
|                 |                       | -          | 400 ppm                 | 984 mg/m3  | STEL         | 15min         |                    |
| 67-63-0         | Isopropanol           | -          | 200 ppm                 |            | TWA          | -             | BC                 |
|                 |                       | -          | 400 ppm                 |            | STEL         | -             |                    |

### Exposure controls

Engineering measures: Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapors.

Personal protection: Personal protection equipment should be chosen according to relevant standards and in discussion with the supplier of the personal protective equipment.

Respiratory equipment: In case of inadequate ventilation and work of brief duration, use suitable respiratory equipment. Use respiratory equipment with gas filter, type A2.

Hand protection: Wear protective gloves. Nitrile gloves are recommended. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

Eye protection: Wear goggles/face shield.

Skin protection: Wear apron or protective clothing in case of splashes.

Environmental Exposure Controls: Not available.

# SAFETY DATA SHEET

|                |                     |             |            |
|----------------|---------------------|-------------|------------|
| Product name:  | DP-LUBRICANT YELLOW | Page:       | 7/12       |
| Revision Date: | 2018-11-07          | Print date: | 2018-11-07 |
| Document No.:  | M0119               | SDS-ID:     | CA-EN/19.0 |

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

(\*)

|   |   |
|---|---|
| <u>Form:</u>                                    | Liquid.   |
| <u>Colour:</u>                                  | Yellow  |
| <u>Odour:</u>                                   | odour of alcohol                                      |
| <u>Odour threshold:</u>                         | Not available.  |
| <u>pH:</u>                                      | Not applicable.                                       |
| <u>Melting point:</u>                           | Not available.  |
| <u>Boiling point:</u>                           | Not available.  |
| <u>Flash point:</u>                             | 13°C  |
| <u>Evaporation rate:</u>                        | 78 - 82°C   |
| <u>Flammability (solid, gas):</u>               | Not available.  |
| <u>Explosion limits:</u>                        | Not available.  |
| <u>Vapour pressure:</u>                         | Not available.  |
| <u>Vapour density:</u>                          | Not available.  |
| <u>Relative density:</u>                        | 0,887   |
| <u>Solubility:</u>                              | Miscible with water.                                  |
| <u>Partition coefficient (n-octanol/water):</u> | Not available.  |
| <u>Auto-ignition temperature (°C):</u>          | Not available.  |
| <u>Decomposition temperature (°C):</u>          | Not available.  |
| <u>Viscosity:</u>                               | Not available.  |
| <u>Explosive properties:</u>                    | Not available.  |
| <u>Oxidising properties:</u>                    | Not available.  |
| <b><u>Other information</u></b>                 |   |
| <u>Other data:</u>                              | Volatile Organic Compound (VOC): 841 g/l (calculated) |

---

# SAFETY DATA SHEET

|                |                     |             |            |
|----------------|---------------------|-------------|------------|
| Product name:  | DP-LUBRICANT YELLOW | Page:       | 8/12       |
| Revision Date: | 2018-11-07          | Print date: | 2018-11-07 |
| Document No.:  | M0119               | SDS-ID:     | CA-EN/19.0 |

---

## 10. STABILITY AND REACTIVITY

### Reactivity

Reactivity: No data available.

### Chemical stability

Stability: Stable under normal temperature conditions.

### Possibility of hazardous reactions

Hazardous Reactions: No data available.

### Conditions to avoid

Conditions/materials to avoid: Direct sunlight. Keep away from heat, sparks and open flame.

### Incompatible materials

Incompatible materials: Oxidizing agents.

### Hazardous decomposition products

Hazardous decomposition products: No information available.

---

# SAFETY DATA SHEET

|                |                     |             |            |
|----------------|---------------------|-------------|------------|
| Product name:  | DP-LUBRICANT YELLOW | Page:       | 9/12       |
| Revision Date: | 2018-11-07          | Print date: | 2018-11-07 |
| Document No.:  | M0119               | SDS-ID:     | CA-EN/19.0 |

---

## 11. TOXICOLOGICAL INFORMATION

### Information on toxicological effects

In case of insufficient ventilation, extensive use may cause the damage described below.

|   |   |
|---|---|
| <u>Acute Toxicity (Oral):</u>             | Based on available data, the classification criteria are not met.   |
| <u>Acute Toxicity (Dermal):</u>           | Based on available data, the classification criteria are not met.   |
| <u>Acute Toxicity (Inhalation):</u>       | Based on available data, the classification criteria are not met.   |
| <u>Skin Corrosion/Irritation:</u>         | Based on available data, the classification criteria are not met.   |
| <u>Serious eye damage/irritation:</u>     | Causes serious eye irritation.  |
| <u>Respiratory or skin sensitization:</u> | Based on available data, the classification criteria are not met.   |
| <u>Germ cell mutagenicity:</u>            | Based on available data, the classification criteria are not met.   |
| <u>Carcinogenicity:</u>                   | Based on available data, the classification criteria are not met.<br>National Toxicology Program (NTP): No.<br>IARC Cancer Review: Group 3 for 2-Propanol.  |
| <u>Reproductive Toxicity:</u>             | Based on available data, the classification criteria are not met.   |
| <u>STOT - Single exposure:</u>            | Based on available data, the classification criteria are not met.   |
| <u>STOT - Repeated exposure:</u>          | Based on available data, the classification criteria are not met.   |
| <u>Aspiration hazard:</u>                 | Based on available data, the classification criteria are not met.   |
| <u>Inhalation:</u>                        | Small quantities: Vapors may irritate throat and respiratory system and cause coughing.<br>Large quantities: Vapors may irritate throat and respiratory system and cause headache, dizziness and dullness. Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication. In serious cases, unconsciousness and permanent damage to the nervous system, including the brain, and liver may be seen. |
| <u>Skin contact:</u>                      | Prolonged contact may cause redness, irritation and dry skin. Contains 2-propanol which may penetrate the skin.   |
| <u>Ingestion:</u>                         | May irritate and cause malaise.   |
| <u>Specific effects:</u>                  | Prolonged or frequent inhalation of vapors in high concentrations may cause permanent damage to the nervous system, including the brain.  |

# SAFETY DATA SHEET

|                |                     |             |            |
|----------------|---------------------|-------------|------------|
| Product name:  | DP-LUBRICANT YELLOW | Page:       | 10/12      |
| Revision Date: | 2018-11-07          | Print date: | 2018-11-07 |
| Document No.:  | M0119               | SDS-ID:     | CA-EN/19.0 |

---

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Ecotoxicity: The product is not expected to be hazardous to the environment.

### Persistence and degradability

Degradability: The product is 80% biodegradable.

### Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation: Is not expected to be bio-accumulable.

### Mobility in soil

Mobility: No data available.

### Results of PBT and vPvB assessment

PBT/vPvB: No information available.

### Other adverse effects

Other adverse effects: No information available.

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Waste from residues: Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Contaminated packaging: Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

---

# SAFETY DATA SHEET

|                |                     |             |            |
|----------------|---------------------|-------------|------------|
| Product name:  | DP-LUBRICANT YELLOW | Page:       | 11/12      |
| Revision Date: | 2018-11-07          | Print date: | 2018-11-07 |
| Document No.:  | M0119               | SDS-ID:     | CA-EN/19.0 |

---

## 14. TRANSPORT INFORMATION

The product is covered by international regulation on the transport of dangerous goods (IMDG, IATA).

### UN number

UN-No: 1993

### UN proper shipping name

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S (Ethanol, Isopropylalcohol Mixture)

Additional IMDG information:

EmS: F-E , S-E

MFAG: 1

### Transport hazard class(es)

Class: 3

### Packing group

PG: II

### Environmental hazards

Marine pollutant: No.

Environmentally Hazardous substance: No.

### Special precautions for user

Special precautions: None known.

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk: Not relevant

---

# SAFETY DATA SHEET

|                |                     |             |            |
|----------------|---------------------|-------------|------------|
| Product name:  | DP-LUBRICANT YELLOW | Page:       | 12/12      |
| Revision Date: | 2018-11-07          | Print date: | 2018-11-07 |
| Document No.:  | M0119               | SDS-ID:     | CA-EN/19.0 |

## 15. REGULATORY INFORMATION

### Safety, health and environmental regulations specific to the product

Special provisions: This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.  
DSL: All chemicals included in the product are DSL listed or exempt.

National regulation: Hazardous Products Regulations, with amendments.  
Canadian Environmental Protection Act, Reporting for the Domestic Substances List (DSL), with amendments.  
U.S. Department of health and human services: 2011 - Report on Carcinogens - 12th Edition.  
International Agency for Research on Cancer (IARC): IARC Monographs on the Evaluation of Carcinogenic Risks to Humans. Lyon: IARC, World Health Organization.  
British Columbia: Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, with amendments (2015).  
Ontario: Control of Exposure to Biological or Chemical Agents R.R.O. 1990, Reg. 833, with amendments (2016).  
Quebec: Regulation respecting the quality of the work environment, with amendments (2013-12-13).  
Alberta: Occupational Health and Safety Code 2009.

## 16. OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

The following sections contain revisions or new statements: 6, 9.

The (\*) indicates the changes made with respect to the previous version.

Approved by DHI.



Additional information: Classification according to WHMIS 2015:  
Calculation method.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark.  
[www.dhigroup.com](http://www.dhigroup.com).