

Product name:	PRONTOFIX HARDENER	Page:	1/11
Revision:	2020-02-18	Print date:	2020-02-18
Document No.:	M0225	SDS-ID:	GB-EN/2.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier		
Product name:	PRONTOFIX HARDENER	
	Cat. No. 40200108, 40200110 (and mixed with ProntoFix Accelerator in the recommended ratio)	
Container size:	280 ml, 500 ml	
1.2. Relevant identified uses of	of the substance or mixture and uses advised against	
Application:	For embedding and impregnation of materialographic specimens	
Uses advised against:	No specific uses advised against are identified. (*)	
1.3. Details of the supplier of t	the safety data sheet	
<u>Supplier:</u>	Struers ApS Pederstrupvej 84 DK-2750 Ballerup Tel:+45 44 600 800	
Responsible for safety data sheet authoring:	Responsible for safety data sheet authoring: DHI Any questions to the contents of this safety data sheet should be sent to: struers@struers.dk	
1.4. Emergency telephone number		
	NHS: 111	

+45 44 600 800 (Only during office hours)

Product name:	PRONTOFIX HARDENER	Page:	2/11
Revision:	2020-02-18	Print date:	2020-02-18
Document No.:	M0225	SDS-ID:	GB-EN/2.0

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

<u>CLP:</u>	Acute Tox. 4;H302 Acute Tox. 4;H332
	Skin Corr. 1A;H314
	Eye Dam. 1;H318
	Skin Sens. 1;H317
	Repr. 2;H361f
	Aquatic Acute 1;H400
	Aquatic Chronic 1;H410

2.2. Label elements



	Danger
<u>Contains:</u>	4-tert-Butylphenol m-Phenylenebis(methylamine) 2-Methyl-1,5-pentamethylen-diamine Amines, polyethylenepoly-, triethylenetetramine fraction
H302 + H332	Harmful if swallowed or if inhaled.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H361f	Suspected of damaging fertility.
H410	Very toxic to aquatic life with long lasting effects.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P501	Dispose of contents/container in accordance with local regulations.
2.3. Other hazards	

Vapours are corrosive. After 24-36 hours, injured persons may develop serious shortness of breath and lung oedema.

<u>PBT/vPvB:</u> Not Classified as PBT/vPvB by current EU criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Product name:	PRONTOFIX HARDENER	Page:	3/11
Revision:	2020-02-18	Print date:	2020-02-18
Document No.:	M0225	SDS-ID:	GB-EN/2.0

Notes:

The product contains: Amines.					
CLP:					
<u>%:</u>	CAS-No.:	<u>EC No.:</u>	<u>REACH Reg.</u> <u>No:</u>	Chemical name:	Hazard classification:
15-<40	98-54-4	202-679-0	01-2119489419- 21-xxxx	4-tert-Butylphenol	Skin Irrit. 2;H315 Eye Dam. 1;H318 Repr. 2;H361f Aquatic Acute 1;H400 Aquatic Chronic 1;H410
10-<25	1477-55-0	216-032-5	01-2119480150- 50-xxxx	m-Phenylenebis (methylamine)	Acute Tox. 4;H302 Acute Tox. 4;H312 Acute Tox. 4;H332 Skin Corr. 1B;H314 Skin Sens. 1;H317 Aquatic Chronic 3;H412
15-<25	90640-67-8	292-588-2	01-2119487919- 13-xxxx	Amines, polyethylenepoly-, triethylenetetramine fraction	Acute Tox. 4;H302 Acute Tox. 4;H312 Skin Corr. 1B;H314 Eye Dam. 1;H318 Skin Sens. 1;H317 Aquatic Chronic 3;H412
10-<20	15520-10-2	239-556-6	01-2119976310- 41-xxxx	2-Methyl-1,5-pentamethylen- diamine	Acute Tox. 4;H302 Acute Tox. 4;H312 Acute Tox. 4;H332 Skin Corr. 1A;H314 Eye Dam. 1;H318 STOT SE 3;H335

References:

The full text for all hazard statements is displayed in section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

<u></u>		
Inhalation:	Move injured person into fresh air immediately. Call an ambulance. Be aware that symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Bring these instructions.	
<u>Skin contact:</u>	Flush immediately with plenty of water and remove contaminated clothing. Call an ambulance, continue to rinse during transportation to hospital and bring these instructions.	
<u>Eye contact:</u>	Immediately flush with plenty of water. Remove any contact lenses and open eyes wide apart. Call an ambulance and continue flushing during transportation to hospital. Bring these instructions.	
Ingestion:	Immediately call a Poison Center/doctor. Rinse mouth. Do not induce vomiting. Do not drink anything without first consulting a doctor. Have these instructions at hand.	
4.2. Most important symptoms and effects, both acute and delayed		
Symptoms/effects:	See section 11 for more detailed information on health effects and symptoms.	

4.3. Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Treat symptomatically.

Product name:	PRONTOFIX HARDENER	Page:	4/11
Revision:	2020-02-18	Print date:	2020-02-18
Document No.:	M0225	SDS-ID:	GB-EN/2.0

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media: Extinguish with foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture

<u>Specific hazards:</u> During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

<u>Protective equipment for fire-</u> Use air-supplied respirator, gloves and protective goggles. <u>fighters:</u>

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel:	Avoid inhalation of vapours and contact with skin and eyes. For personal protection, see section 8.	
For emergency responders:	No specific recommendations. For personal protection, see section 8.	
6.2. Environmental precautions		
Environmental precautions:	Do not discharge into drains, water courses or onto the ground.	
6.3. Methods and material for containment and cleaning up		

<u>Methods for cleaning up:</u> Dam and absorb spillages with sand, earth or other non-combustible material.

6.4. Reference to other sections

<u>References:</u> For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling advice:	Avoid inhalation of vapours and contact with skin and eyes. Observe good chemical hygiene practices.	
Technical measures:	Wash hands before breaks and before smoking, eating or drinking.	
Technical precautions:	Local exhaust is recommended. First-aid equipment, including eye wash bottle, must be available at the work site.	
7.2. Conditions for safe storage, including any incompatibilities		
Storage conditions:	Store in tightly closed original container in a dry, cool and well-ventilated place.	
7.3. Specific end use(s)		
<u>Specific use(s):</u>	No information available.	

Product name:	PRONTOFIX HARDENER	Page:	5/11
Revision:	2020-02-18	Print date:	2020-02-18
Document No.:	M0225	SDS-ID:	GB-EN/2.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No occupational exposure limit assigned.

8.2. Exposure controls

Engineering measures:	Mix and prepare in a place with efficient exhaust ventilation. An eye wash bottle must be available at the work site. Provide access to washing facilities including soap, skin cleanser and fatty cream.
Personal protection:	Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Respiratory equipment:	In case of inadequate ventilation and work of brief duration, use suitable respiratory equipment. It is recommended to use respiratory equipment with combination filter, type ABEK
Hand protection:	Use disposable gloves protecting against epoxy and amines along with cotton gloves closest to the skin. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. (*)
Eye protection:	Wear goggles/face shield.
Skin protection:	Wear apron or protective clothing in case of splashes.
Hygiene measures:	Remove contaminated clothing and wash the skin thoroughly with soap and water after work. When using do not eat, drink or smoke.
Environmental Exposure Controls:	Not available.

Product name:	PRONTOFIX HARDENER	Page:	6/11
Revision:	2020-02-18	Print date:	2020-02-18
Document No.:	M0225	SDS-ID:	GB-EN/2.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties Form: Liquid. Colour: Yellowish. Amine. Odour: Odour threshold: Not available. pH: Not available. Melting point: Not available. Boiling point: 180 - 300°C >83°C / >181.4°F (*) Flash point: Evaporation rate: Not available. Flammability (solid, gas): Not available. Not available. Explosive limits Not available. Vapour pressure: Not available. Vapour density: Relative density: 0.99 - 1.00 Partially soluble in water. Solubility: Partition coefficient (n-Not available. octanol/water): Auto-ignition Not available. temperature (°C): Decomposition Not available. temperature (°C): 115 - 200 mPa*s Viscosity: Not available. Explosive properties: Oxidising properties: Not available. 9.2. Other information Other data: No information available.

Product name:	PRONTOFIX HARDENER	Page:	7/11
Revision:	2020-02-18	Print date:	2020-02-18
Document No.:	M0225	SDS-ID:	GB-EN/2.0

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity	
Reactivity:	Reacts violently with strong oxidising substances.
10.2. Chemical stability	
<u>Stability:</u>	Stable under normal temperature conditions.
10.3. Possibility of hazardous	reactions
Hazardous Reactions:	None under normal conditions.
10.4. Conditions to avoid	
Conditions/materials to avoid:	Moisture, heating and strong oxidising substances.
10.5. Incompatible materials	
Incompatible materials:	Oxidising materials. Strong acids.
10.6. Hazardous decomposition	on products
Hazardous decomposition products:	When heated, toxic and corrosive vapours/gases may be formed.

Product name:	PRONTOFIX HARDENER	Page:	8/11
Revision:	2020-02-18	Print date:	2020-02-18
Document No.:	M0225	SDS-ID:	GB-EN/2.0

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects Acute Toxicity (Oral): Harmful if swallowed. m-Phenylenebis(methylamine): LD50 (Oral, Rat): 940 mg/kg 2-Methyl-1,5-pentamethylen-diamine: LD50 (Oral, Rat): 1690 mg/kg Acute Toxicity (Dermal): Based on available data, the classification criteria are not met. m-Phenylenebis(methylamine): LD50 (Dermal, Rabbit): 2000 mg/kg 2-Methyl-1,5-pentamethylen-diamine: LD50(Dermal, Rabbit): 1900 mg/kg Harmful if inhaled. Acute Toxicity (Inhalation): Skin Corrosion/Irritation: Causes severe burns. Serious eye damage/irritation: Causes serious eye damage. Respiratory or skin May cause an allergic skin reaction. sensitisation: Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive Toxicity: Suspected of damaging fertility. STOT - Single exposure: May cause respiratory irritation. STOT - Repeated exposure: Based on available data the classification criteria are not met. Aspiration hazard: Based on available data, the classification criteria are not met. Inhalation: Vapours are corrosive. After 24-36 hours, injured persons may develop serious shortness of breath and lung oedema. Ingestion: Strongly corrosive. Even small amounts may be fatal. Symptoms are severe burning pains in mouth, throat and stomach.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity Ecotoxicity: Very toxic to aquatic life with long lasting effects. 12.2. Persistence and degradability Degradability: The degradability of the product has not been stated. 12.3. Bioaccumulative potential No data available on bioaccumulation. **Bioaccumulative potential:** 12.4. Mobility in soil Mobility: No data available. 12.5. Results of PBT and vPvB assessment PBT/vPvB: This product does not contain any PBT or vPvB substances. 12.6. Other adverse effects Other adverse effects: No information available.

Product name:	PRONTOFIX HARDENER	Page:	9/11
Revision:	2020-02-18	Print date:	2020-02-18
Document No.:	M0225	SDS-ID:	GB-EN/2.0

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues:	Dispose of waste and residues in accordance with local authority requirements. Waste is classified as hazardous waste. Note that fully cured material is not considered as hazardous waste.
	EWC-code: 16 05 08

<u>Contaminated packaging:</u> Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

The product is covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

<u>14.1. UN number</u>		
<u>UN-No:</u>	2735	
14.2. UN proper shipping nam	ne la	
Proper Shipping Name:	AMINES, LIQUID, CORROSIVE, N.O.S. (2-Methyl-1,5-pentamethylen-diamine, m-Phenylenebis(methylamine))	
14.3. Transport hazard class(e	<u>es)</u>	
<u>Class:</u>	8	
14.4. Packing group		
<u>PG:</u>	1	
14.5. Environmental hazards		
Marine pollutant:	Yes.	
Environmentally Hazardous substance:	Yes.	
14.6. Special precautions for u	<u>user</u>	
Special precautions:	None known.	
14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code		
Transport in bulk:	Not relevant.	

Product name:	PRONTOFIX HARDENER	Page:	10/11
Revision:	2020-02-18	Print date:	2020-02-18
Document No.:	M0225	SDS-ID:	GB-EN/2.0

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Special provisions:	As a general rule, persons under 18 years of age are not allowed to work with this product. Users must be carefully instructed in the proper work procedure, the dangerous properties of the product and the necessary safety instructions.
National regulation:	 Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, with amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Statutory Instruments 2008 No. 2852 - The REACH Enforcement Regulations 2008. The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. The Management of Health and Safety at Work Regulations 1999 (SI 1999 No. 3242), with amendments. The List of Wastes (England) (Amendment) Regulations 2005. (SI 2005 No. 895).

15.2. Chemical Safety Assessment

CSA status:

No chemical safety assessment has been carried out.

Product name:	PRONTOFIX HARDENER	Page:	11/11
Revision:	2020-02-18	Print date:	2020-02-18
Document No.:	M0225	SDS-ID:	GB-EN/2.0

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

The following sections contain revisions or new statements: 1, 8, 9. The (*) indicates the changes made with respect to the previous version.

Approved by DHI.

Allan Vorup

Additional information:	Classification according to Regulation (EC) No. 1272/2008: Calculation method.
Wording of H-statements:	
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark. www.dhigroup.com.