

Product Data Sheet



Struers ApS
Pederstrupvej 84
2750 Ballerup, Denmark

Phone +45 44 600 800
Fax +45 44 600 803
struers@struers.dk
www.struers.com

Product Name **MD/DP-Floc-T**

Cat. no.	40500423	MD-Floc-T, 200 mm (8") dia.
	40500424	MD-Floc-T, 250 mm (10") dia.
	40500425	MD-Floc-T, 300 mm (12") dia.
	40500426	MD-Floc-T, 350 mm (14") dia.
	40500420	DP-Floc-T, 200 mm (8") dia.
	40500421	DP-Floc-T, 250 mm (10") dia.
	40500422	DP-Floc-T, 300 mm (12") dia.

Revision 21-03-2017

Description Short synthetic nap.

Material Regenerated cellulose fibres glued on a base textile with an adhesive backing / on a metal plate.

Properties DP-Floc-T to be applied on a preparation disc. DP-Floc-T is self-adhesive. MD-Floc-T for magnetic fixation on MD-Disc. Black screen printing on the rear.

Re-usable.

Application For polishing of materialographic specimens. To be used with Struers diamond polishing products and lubricants.

Health and Safety

- Whilst the MD/DP-Floc-T is rotating, ensure hands are kept well clear of the edge and out of the splash bowl.
- Do not exceed a rotational speed of 600 rpm.

To the best of Struers' knowledge, the products listed above do not contain any Substances of Very High Concern (SVHC) according to REACH regulations (amended on 20th June 2016) above 0.1%.

According to OSHA's Hazard Communication Standard (HCS 2012) 29 CFR 1910.1200 paragraph (c) this product is considered an article and defined as "a manufactured item other than a fluid or particle: (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g., minute or trace amounts of a hazardous chemical (as determined under paragraph (d) of this section), and does not pose a physical hazard or health risk to employees".

Therefore this product is exempted from HCS 2012 obligations on classification and labelling under stated normal conditions of use (29 CFR 1910.1200 (b)(6)(v)).

See Instructions for Use for more information.

Skin protection

Wear protective gloves during polishing.


Respiratory Protection

It is recommended that the polishing machine is adequately ventilated during use of MD-Floc-T / DP-Floc-T.

Environmental precautions

Dispose of waste and residues as metal waste in accordance with local authority requirements.

Approved by:



Krista Huggins

Chemical Safety Specialist
Struers ApS.