

SAFETY DATA SHEET



Product name:	DP-LUBRICANT YELLOW	Page:	1/11
Revision Date:	2018-11-07	Print date:	2018-11-07
Document No.:	M0119	SDS-ID:	AU-EN/19.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name: DP-LUBRICANT YELLOW
Cat. No. 40700030

Container size: 1 l

Relevant identified uses of the substance or mixture and uses advised against

Application: Cooling and lubricating agent for grinding and polishing of materialographic specimens.

Details of the supplier of the safety data sheet

Supplier: Struers Australia
27 Mayneview Street
Milton QLD 4064, Australia

Responsible for safety data sheet authoring: Responsible for safety data sheet authoring: DHI
Any questions to the contents of this safety data sheet should be sent to:
struers@struers.dk

Emergency telephone number

Australian Poisons Information Centre: 13 11 26.

+61 7 3512 9600
(Only during office hours)

SAFETY DATA SHEET

Product name:	DP-LUBRICANT YELLOW	Page:	2/11
Revision Date:	2018-11-07	Print date:	2018-11-07
Document No.:	M0119	SDS-ID:	AU-EN/19.0

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

WHS: Flammable liquid - Category 2
Serious eye damage/eye irritation - Category 2

Label elements



Danger

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P280 Wear protective gloves, eye and face protection.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local regulations.

Other hazards

PBT/vPvB: No information available.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

The product contains: organic solvents, lubricants and pigments.

WHS:

<u>%:</u>	<u>CAS-No.:</u>	<u>EC No.:</u>	<u>REACH Reg. No:</u>	<u>Chemical name:</u>	<u>Hazard classification:</u>	<u>Notes:</u>
50-90	64-17-5	200-578-6	01-2119457610-43-xxxx	Ethanol	Flam. Liq. 2;H225 Eye Irrit. 2;H319	
5-<10	67-63-0	200-661-7	01-2119457558-25-xxxx	Propan-2-ol	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	
<0.1	-	-	-	Pigment	-	

References: The full text for all hazard statements is displayed in section 16.

SAFETY DATA SHEET

Product name:	DP-LUBRICANT YELLOW	Page:	3/11
Revision Date:	2018-11-07	Print date:	2018-11-07
Document No.:	M0119	SDS-ID:	AU-EN/19.0

SECTION 4: FIRST AID MEASURES

Description of first aid measures

Burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

Inhalation: Move injured person into fresh air and keep person calm under observation. If uncomfortable: Seek hospital and bring these instructions.

Skin contact: Remove contaminated clothes and rinse skin thoroughly with water.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Continue flushing during transport to hospital. Bring along these instructions.

Ingestion: Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable seek hospital and bring these instructions.

Most important symptoms and effects, both acute and delayed

Symptoms/effects: See section 11 for more detailed information on health effects and symptoms.

Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Extinguishing media: Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards: The product is highly flammable, and explosive vapours/air mixtures may be formed even at normal room temperatures. Vapours may be ignited by a spark, a hot surface or an ember.

Advice for firefighters

Protective equipment for fire-fighters: Use air-supplied respirator during fire fighting.

SAFETY DATA SHEET

Product name:	DP-LUBRICANT YELLOW	Page:	4/11
Revision Date:	2018-11-07	Print date:	2018-11-07
Document No.:	M0119	SDS-ID:	AU-EN/19.0

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Protective equipment: Do not smoke or use open fire, or other sources of ignition. Avoid inhalation of vapours and contact with skin and eyes. For personal protection, see section 8. (*)

Emergency procedures: No specific recommendations. For personal protection, see section 8. (*)

Environmental precautions

Environmental precautions: Do not discharge into drains, water courses or onto the ground.

Methods and material for containment and cleaning up

Spill Cleanup Methods: Large quantities of concentrate should not be discharged into the drain but removed with absorbing material. Do not use sawdust or other combustible material.

Reference to other sections

References: For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Safe handling advice: Avoid inhalation of vapours and contact with skin and eyes. Observe good chemical hygiene practices. Take precautionary measures against static discharges.

Technical measures: Do not smoke or use open fire or other sources of ignition.

Technical precautions: Local exhaust is recommended.

Conditions for safe storage, including any incompatibilities

Technical measures for safe storage: Follow rules for flammable liquids.

Storage conditions: Store in a cool and well-ventilated place. Avoid contact with oxidising agents.

Specific end use(s)

Specific use(s): No information available.

SAFETY DATA SHEET

Product name:	DP-LUBRICANT YELLOW	Page:	5/11
Revision Date:	2018-11-07	Print date:	2018-11-07
Document No.:	M0119	SDS-ID:	AU-EN/19.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational exposure limits:

<u>CAS-No.:</u>	<u>Chemical name:</u>	<u>As:</u>	<u>Exposure limits:</u>		<u>Type:</u>	<u>Notes:</u>	<u>References:</u>
67-63-0	Isopropyl alcohol	-	400 ppm	983 mg/m3	TWA	-	NOHSC
		-	500 ppm	1230 mg/m3	STEL	15min	
64-17-5	Ethyl alcohol	-	1000 ppm	1880 mg/m3	TWA	-	NOHSC

Exposure controls

Engineering measures: Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

Personal protection: Personal protection equipment should be chosen according to relevant AS/NZS standards and in discussion with the supplier of the personal protective equipment.

Respiratory equipment: In case of inadequate ventilation and work of brief duration, use suitable respiratory equipment. Use respiratory equipment with gas filter, type A2.

Hand protection: Wear protective gloves. Nitrile gloves are recommended. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

Eye protection: Wear goggles/face shield.

Skin protection: Wear apron or protective clothing in case of splashes.

Environmental Exposure Controls: Not available.

SAFETY DATA SHEET

Product name:	DP-LUBRICANT YELLOW	Page:	6/11
Revision Date:	2018-11-07	Print date:	2018-11-07
Document No.:	M0119	SDS-ID:	AU-EN/19.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

(*)

<u>Form:</u>	Liquid.
<u>Colour:</u>	Yellow.
<u>Odour:</u>	odour of alcohol
<u>Odour threshold:</u>	Not available.
<u>pH:</u>	Not applicable.
<u>Melting point:</u>	Not available.
<u>Boiling point:</u>	Not available.
<u>Flash point:</u>	13°C
<u>Evaporation rate:</u>	78 - 82°C
<u>Flammability (solid, gas):</u>	Not available.
<u>Explosion limits:</u>	Not available.
<u>Vapour pressure:</u>	Not available.
<u>Vapour density:</u>	Not available.
<u>Relative density:</u>	0,887
<u>Solubility:</u>	Miscible with water.
<u>Partition coefficient (n-octanol/water):</u>	Not available.
<u>Auto-ignition temperature (°C):</u>	Not available.
<u>Decomposition temperature (°C):</u>	Not available.
<u>Viscosity:</u>	Not available.
<u>Explosive properties:</u>	Not available.
<u>Oxidising properties:</u>	Not available.
<u>Other information</u>	
<u>Other data:</u>	Volatile Organic Compound (VOC): 841 g/l (calculated)

SAFETY DATA SHEET

Product name:	DP-LUBRICANT YELLOW	Page:	7/11
Revision Date:	2018-11-07	Print date:	2018-11-07
Document No.:	M0119	SDS-ID:	AU-EN/19.0

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Reactivity: No data available.

Chemical stability

Stability: Stable under normal temperature conditions.

Possibility of hazardous reactions

Hazardous Reactions: No data available.

Conditions to avoid

Conditions/materials to avoid: Direct sunlight. Keep away from heat, sparks and open flame.

Incompatible materials

Incompatible materials: Oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products: No information available.

SAFETY DATA SHEET

Product name:	DP-LUBRICANT YELLOW	Page:	8/11
Revision Date:	2018-11-07	Print date:	2018-11-07
Document No.:	M0119	SDS-ID:	AU-EN/19.0

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects

In case of insufficient ventilation, extensive use may cause the damage described below.

<u>Acute Toxicity (Oral):</u>	Based on available data, the classification criteria are not met.
<u>Acute Toxicity (Dermal):</u>	Based on available data, the classification criteria are not met.
<u>Acute Toxicity (Inhalation):</u>	Based on available data, the classification criteria are not met.
<u>Skin Corrosion/Irritation:</u>	Based on available data, the classification criteria are not met.
<u>Serious eye damage/irritation:</u>	Causes serious eye irritation.
<u>Respiratory or skin sensitisation:</u>	Based on available data, the classification criteria are not met.
<u>Germ cell mutagenicity:</u>	Based on available data, the classification criteria are not met.
<u>Carcinogenicity:</u>	Based on available data, the classification criteria are not met. National Toxicology Program (NTP): No. IARC Cancer Review: Group 3 for 2-Propanol.
<u>Reproductive Toxicity:</u>	Based on available data, the classification criteria are not met.
<u>STOT - Single exposure:</u>	Based on available data, the classification criteria are not met.
<u>STOT - Repeated exposure:</u>	Based on available data, the classification criteria are not met.
<u>Aspiration hazard:</u>	Based on available data, the classification criteria are not met.
<u>Inhalation:</u>	Small quantities: Vapours may irritate throat and respiratory system and cause coughing. Large quantities: Vapours may irritate throat and respiratory system and cause headache, dizziness and dullness. Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication. In serious cases, unconsciousness and permanent damage to the nervous system, including the brain, and liver may be seen.
<u>Skin contact:</u>	Prolonged contact may cause redness, irritation and dry skin. Contains 2-propanol which may penetrate the skin.
<u>Ingestion:</u>	May irritate and cause malaise.
<u>Specific effects:</u>	Prolonged or frequent inhalation of vapours in high concentrations may cause permanent damage to the nervous system, including the brain.

SAFETY DATA SHEET

Product name:	DP-LUBRICANT YELLOW	Page:	9/11
Revision Date:	2018-11-07	Print date:	2018-11-07
Document No.:	M0119	SDS-ID:	AU-EN/19.0

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecotoxicity: The product is not expected to be hazardous to the environment.

Persistence and degradability

Degradability: The product is 80% biodegradable.

Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation: Is not expected to be bioaccumulable.

Mobility in soil

Mobility: No data available.

Results of PBT and vPvB assessment

PBT/vPvB: No information available.

Other adverse effects

Other adverse effects: No information available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues: Dispose of waste and residues in accordance with local authority requirements.
For personal protection, see section 8.
Hazardous characteristics of waste: H3 (Flammable liquids) (*)

Contaminated packaging: Dispose of waste and residues in accordance with local authority requirements.

SAFETY DATA SHEET

Product name:	DP-LUBRICANT YELLOW	Page:	10/11
Revision Date:	2018-11-07	Print date:	2018-11-07
Document No.:	M0119	SDS-ID:	AU-EN/19.0

SECTION 14: TRANSPORT INFORMATION

The product is covered by international regulation on the transport of dangerous goods (IMDG, IATA).

UN number

UN-No: 1993

UN proper shipping name

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S (Ethanol, Isopropylalcohol Mixture)

Additional IMDG information:

EmS: F-E , S-E

MFAG: 1

Transport hazard class(es)

Class: 3

Packing group

PG: II

Environmental hazards

Marine pollutant: No.

Environmentally Hazardous substance: No.

Special precautions for user

Special precautions: None known.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk: Not relevant.

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Special provisions: AICS: Listed.

National regulation: Work Health and Safety Regulations 2011, with amendments.
National model Code of Practice for the Labelling of Workplace Hazardous Chemicals (2011), with amendments.
National model Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals (2011), with amendments.
Workplace exposure standards for airborne contaminants (2018).
Hazardous Waste (Regulation of Exports and Imports) Act 1989, with amendments.
The Industrial Chemicals (Notification and Assessment) Act 1989, as amended.

SAFETY DATA SHEET

Product name:	DP-LUBRICANT YELLOW	Page:	11/11
Revision Date:	2018-11-07	Print date:	2018-11-07
Document No.:	M0119	SDS-ID:	AU-EN/19.0

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

The following sections contain revisions or new statements: 6, 9, 13.

The (*) indicates the changes made with respect to the previous version.

Approved by DHI.



Additional information:

Classification according to WHS Regulations 2011:
Calculation method.

Wording of H-statements:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark.
www.dhigroup.com.